



Petroleum Transfer Hose

Blacksnake® (Curb Pump - Hardwall) (Specification 3624)

Nom. I.D. (In.)	⊖ (mm)	Nom. O.D. (In.)	⊖ (mm)	Max. W.P. (psi)	⊕ (MPa)	Suction (In. Hg)	⊖ (mm Hg)	Min. Bend Radius (In.)	⊖ (mm)	Wt. Per Ft. (Lbs.)	⊖ (Kg)	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
5/8	15.9	1.00	25.4	150	1.03	30.0	762	6.0	152	.37	.17	Reel	X	3624-0001	\$8.52
3/4	19.1	1.13	28.7	150	1.03	30.0	762	6.0	152	.42	.19	Reel	X	3624-0002	8.94
1	25.4	1.38	35.1	150	1.03	30.0	762	8.0	203	.57	.26	Reel	X	3624-0003	13.13

RECOMMENDED FOR: Dispensing all types of commercial gasolines, or other petroleum based products, from service station pumps. A heavy duty hardwall hose which does not collapse in reel use or behind the nozzle in heavy duty service.

TEMPERATURE: -40°F to +120°F (-40°C to +49°C) continuous service.

CONSTRUCTION:
Tube: Type C (Nitrile). Black.
Reinforcement: Braided, high tensile steel wire.
Cover: Type J (CPE). Black. 5/8" and 3/4" smooth, 1" wrapped.
Design Factor: 4:1

COUPLINGS: 24. Reference the Hose Coupling Section.

PACKAGING: 5/8" through 1": Packaged 500' per reel. Maximum 5 pieces. Minimum length 12'.

BRANDING: Continuous transfer label. Example: "GATES® BLACKSNAKE® 3/4 Inch (19.1mm) 1 wire braid (UL) Listed Gasoline Hose Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: Underwriters Laboratories Standard No. 330 (USA) and ULC-S612-99 (Canada).
Tube: ARPM (Class A) High oil resistance.

ACID-
CHEMICAL

AIR AND
MULTI-
PURPOSE

FOOD AND
BEVERAGE

MARINE

MATERIAL
HANDLING

MINING

OILFIELD

PETROLEUM
TRANSFER

PRESSURE
WASHER

STEAM

WATER

CLAMPS

COUPLINGS
AND
FERRULES

HOSE FINDER

CHEMICAL
RESISTANCE
TABLE

