



Pressure Washer

PowerClean™ 1 Wire Braid

(Specification 4657, KB, KG, KK, KR, KY, PB, PG, PY)

PowerClean™ 3500

Color	Nom. I.D.	Nom. O.D.	Max. W.P.	Suction	Min. Bend Radius	Wt. Per Ft.	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.					
	(In.)										(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)
Black	1/4	6.4	.53	3500	24.13	30.0	762	4.0	102	.15	.07	Reel	X	4657-2400	\$3.00
Black	1/4	6.4	.53	3500	24.13	30.0	762	4.0	102	.15	.07	Lg. Reel	X	4657-2418	2.88
Blue	1/4	6.4	.53	3500	24.13	30.0	762	4.0	102	.15	.07	Reel	X	4657-2419	3.15
Blue	1/4	6.4	.53	3500	24.13	30.0	762	4.0	102	.17	.07	Lg. Reel	5,000 ft.	4657-2562	3.05
Gray	1/4	6.4	.53	3500	24.13	30.0	762	4.0	102	.15	.07	Reel	X	4657-2420	3.15
Yellow	1/4	6.4	.53	3500	24.13	30.0	762	4.0	102	.15	.07	Reel	5,000 ft.	4657-2421	3.15

PowerClean™ 4000

Color	Nom. I.D.	Nom. O.D.	Max. W.P.	Suction	Min. Bend Radius	Wt. Per Ft.	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.					
	(In.)										(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)
Black	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.23	.10	Reel	X	4657-2225	\$4.34
Black	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.23	.10	Lg. Reel	X	4657-2405	4.17
Blue	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.23	.10	Reel	X	4657-2422	4.55
Red	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.25	.10	Lg. Reel	5,000 ft.	4657-2499	4.55
Gray	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.23	.10	Reel	X	4657-2423	4.55
Gray	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.25	.10	Lg. Reel	5,000 ft.	4657-2156	4.55
Yellow	3/8	9.5	.68	4000	27.58	30.0	762	5.0	127	.23	.10	Reel	5,000 ft.	4657-2424	4.55

RECOMMENDED FOR: Heavy-duty use on hot and cold water high pressure cleaning equipment where heavy duty service is required.

CAUTION: Use Bend Restrictors to extend service life. Not recommended for steam service.

TEMPERATURE: -40°F to +250°F (-40°C to +121°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

CONSTRUCTION:
Tube: Type C (Nitrile). Black. Specially compounded to handle high pressure water service.
Reinforcement: High tensile steel one-wire braid.
Cover: Type C2 (Modified Nitrile). Black, Blue, Gray, Red, Yellow. Specially compounded to handle pressure washer environment. (Blue, Gray, Red and Yellow covers are non-marking).
Design Factor: 4:1

COUPLINGS: 74 MegaCrimp® couplings. Reference the Hose Coupling Section.

PACKAGING: 1/4" through 1/2": Packaged in 1000' large reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.
 1/4" through 1/2": Packaged in 300' reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.

BRANDING: Continuous transfer label. Example: "GATES® 3/8 Inch PowerClean™ 3000 Max WP 3000 PSI Not For Steam Service Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNANT LENGTHS: None.

ACID-CHEMICAL

AIR AND MULTI-PURPOSE

FOOD AND BEVERAGE

MARINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM TRANSFER

PRESSURE WASHER

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE



Powering Progress.

gates.com/industrialhose