



Water Hose

Dolphin®
(Specification 3137T)

| Nom. I.D. | ⊖ | Nom. O.D. | ⊕ | Max. W.P. | ⊕ | Suction | ⊖ | Min. Bend Radius | ⊕ | Wt. Per Ft. | ⊕ | Standard Pack | Stock (X) or Minimum Order Qty. | Gates Item No. | List Price Per Ft. |
|-----------|-------|-----------|-------|-----------|-------|----------|---------|------------------|------|-------------|------|---------------|---------------------------------|----------------|--------------------|
| (In.) | (mm) | (In.) | (mm) | (psi) | (MPa) | (In. Hg) | (mm Hg) | (In.) | (mm) | (Lbs.) | (Kg) | | | | |
| 1 1/4 | 31.8 | 1.53 | 38.9 | 150 | 1.03 | — | — | — | — | .37 | .17 | 100 ft. | X | 3137-0884 | \$8.03 |
| 1 1/2 | 38.1 | 1.78 | 45.2 | 150 | 1.03 | — | — | — | — | .43 | .20 | 100 ft. | X | 3137-0883 | 8.78 |
| 1 1/2 | 38.1 | 1.78 | 45.2 | 150 | 1.03 | — | — | — | — | .43 | .20 | 200 ft. | 400 ft. | 3137-0898 | 8.78 |
| 2 | 50.8 | 2.32 | 58.9 | 150 | 1.03 | — | — | — | — | .65 | .30 | 100 ft. | X | 3137-0885 | 9.75 |
| 2 | 50.8 | 2.32 | 58.9 | 150 | 1.03 | — | — | — | — | .65 | .30 | 200 ft. | 400 ft. | 3137-0905 | 9.75 |
| 2 1/2 | 63.5 | 2.82 | 71.6 | 150 | 1.03 | — | — | — | — | .80 | .36 | 100 ft. | X | 3137-0888 | 12.68 |
| 3 | 76.2 | 3.36 | 85.3 | 150 | 1.03 | — | — | — | — | 1.08 | .49 | 100 ft. | X | 3137-0886 | 14.25 |
| 3 | 76.2 | 3.36 | 85.3 | 150 | 1.03 | — | — | — | — | 1.08 | .49 | 200 ft. | 400 ft. | 3137-0895 | 14.25 |
| 4 | 101.6 | 4.36 | 111.7 | 150 | 1.03 | — | — | — | — | 1.41 | .64 | 100 ft. | X | 3137-0889 | 18.83 |
| 4 | 101.6 | 4.36 | 111.7 | 150 | 1.03 | — | — | — | — | 4.41 | 2.00 | 200 ft. | 400 ft. | 3137-0896 | 18.83 |
| 6 | 152.4 | 6.38 | 162.1 | 125 | .86 | — | — | — | — | 2.09 | .95 | 100 ft. | X | 3137-0890 | 33.30 |
| 6 | 152.4 | 6.38 | 162.1 | 125 | .86 | — | — | — | — | 2.09 | .95 | 200 ft. | 400 ft. | 3137-0892 | 33.30 |
| 6 5/8 | 168.3 | 7.12 | 180.8 | 90 | .62 | — | — | — | — | 3.00 | 1.36 | 100 ft. | 200 ft. | 3137-1269 | 45.23 |

RECOMMENDED FOR: Medium to light duty water discharge for agricultural, construction and industrial applications. EPDM tube designed to handle a variety of liquids including Lasso*, Lasso II* and Freedom*.

TEMPERATURE: -40°F to +180°F (-40°C to +82°C).

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile.
Cover: Type P (EPDM). Black with green spiral stripe.
Design Factor: 3:1

COUPLINGS: 5, 6, 7, 8, 49 or 78 all sizes. Reference the Hose Coupling Section.
NOTE: 3:1 Safety Factor for Burst Pressure to Working Pressure is reduced when the temperature increases.

PACKAGING: All lengths coiled and wrapped in polyethylene.

BRANDING: Continuous transfer label. Example: "GATES® Dolphin® Water Discharge 150 PSI (1.03MPa) WP Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 400 feet for sizes through 4" I.D. and 200 feet for sizes above 4" I.D. If a special transfer label is required, contact Gates Corporation for minimum quantity.

Specific cut lengths available through the Cut Length Program. Contact Customer Service for details.

REMNANT LENGTHS: Remnant lengths are sometimes available in popular sizes at a discount. Contact Gates Corporation for pricing, order requirements and availability.

*Lasso®, Lasso II® and Freedom® are Registered Trademarks of Monsanto.

ACID-CHEMICAL

AIR AND MULTI-PURPOSE

FOOD AND BEVERAGE

MARINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM TRANSFER

PRESSURE WASHER

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE



Powering Progress.

gates.com/industrialhose