

## Air and Multi-Purpose Hose

### Plant Master® Plus (200-300)

Formerly - Duro Flex®



AGRICULTURE
AIR BREATHING
AIR DUCT
<b>AIR AND MULTI-PURPOSE</b>
CHEMICAL
FOOD AND BEVERAGE
MARINE AND ENGINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM
PRESSURE WASH AND WASHDOWN
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO (ft)	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)					
Black	2	50.8	200	4.0	16.5	1.32	100	Ctn	T	Stock	3206-3968	\$20.67
Red	1/4	6.4	250	30.0	2.0	.10	500	Reel	XX	Stock	3200-0002	1.85
	1/4	6.4	250	30.0	2.0	.09	500	Reel	T	Stock	3200-0202	2.04
Red	1/4	6.4	300	30.0	2.0	.12	500	Reel	XX	Stock	3200-0003	2.00
	3/8	9.5	250	30.0	3.0	.14	500	Reel	XX	Stock	3200-0006	2.34
	3/8	9.5	250	30.0	3.0	.14	500	Reel	T	Stock	3200-0206	2.57
Red	3/8	9.5	300	30.0	3.0	.18	500	Reel	XX	Stock	3200-0007	2.60
	3/8	9.5	300	30.0	3.0	.18	500	Reel	T	Stock	3200-0207	2.86
	1/2	12.7	250	25.0	4.0	.19	500	Reel	XX	Stock	3200-0008	2.78
Red	1/2	12.7	250	25.0	4.0	.25	500	Reel	T	Stock	3200-0208	3.06
	1/2	12.7	300	25.0	4.0	.25	500	Reel	XX	Stock	3200-0009	3.53
	1/2	12.7	300	25.0	4.0	.22	500	Reel	T	Stock	3200-0209	3.88
Red	5/8	15.9	250	20.0	5.0	.27	500	Reel	XX	MTO	3200-0010	3.86
	5/8	15.9	300	20.0	5.0	.30	500	Reel	XX	Stock	3200-0011	4.52
	5/8	15.9	250	20.0	5.0	.27	500	Reel	T	Stock	3200-0210	4.25
Red	3/4	19.1	250	20.0	5.0	.36	50	Bulk	200	MTO	3200-5012	3.99
	3/4	19.1	250	20.0	5.0	.36	500	Reel	XX	Stock	3200-0012	3.99
	3/4	19.1	300	20.0	5.0	.36	500	Reel	XX	Stock	3200-0013	4.83
Red	3/4	19.1	250	20.0	5.0	.35	500	Reel	T	Stock	3200-0212	4.39
	3/4	19.1	300	20.0	5.0	.36	500	Reel	T	Stock	3200-0213	5.31
	1	25.4	250	10.0	8.0	.54	400	Reel	XX	Stock	3200-0014	5.87
Red	1 1/4	31.8	250	10.0	10.0	.67	200	Reel	XX	Stock	3200-0015	11.58
	1 3/8	34.9	250	10.0	11.0	.86	250	Reel	XX	MTO	3200-0237	14.35
	1 1/2	38.1	250	10.0	12.0	.79	200	Reel	XX	Stock	3200-0016	12.08
Red	2	50.8	200	4.0	16.5	1.28	100	Ctn	T	Stock	3200-1279	20.67

NOTE: Pkg Code T=One piece continuous length reel. Pkg Code XX=Two piece reel, 50 ft increments, no length less than 50 ft.

- RECOMMENDED FOR:** Applications requiring maximum flexibility and good resistance to air, water and heat. For SAE oils intermittent contact only.
- TEMPERATURE:** -40°F to +200°F (-40°C to +93°C) continuous service.
- CONSTRUCTION:** **Tube:** Type B1 (Specially compounded elastomer). Black.  
**Reinforcement:** Synthetic, high tensile textile cord.  
**Cover:** Type D3 (Specially compounded elastomer). For 2" Black only.  
Type P (EPDM). Red. All sizes through 1/2" have perforated cover.
- Design Factor:** 3:1
- COUPLINGS:** 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.
- STANDARDS:** **Tube:** ARPM (Class B) Medium oil-resistance.  
**Cover:** ARPM (Class C) Limited oil-resistance.