

## Chemical Hose

### Chem Master™ DEF Transfer 350

Formerly - Diesel Exhaust Fluid



AGRICULTURE
AIR BREATHING
AIR DUCT
AIR AND MULTI-PURPOSE
CHEMICAL
FOOD AND BEVERAGE
MARINE AND ENGINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM
PRESSURE WASH AND WASHDOWN
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)			(ft)		
Black	3/4	19.1	350	15.0	4.0	.32	550	Reel	GG	Stock	4217-0310	\$6.76
Black	1	25.4	350	10.0	6.0	1.00	400	Reel	CC	Stock	4217-0311	9.82

**RECOMMENDED FOR:** DEF dispensing tank fill hose. Transfer of urea solutions such as ADBLUE.

**TEMPERATURE:** -40°F to +212°F (-40°C to +100°C) continuous service.

**CONSTRUCTION:**  
**Tube:** Type P (EPDM), Black – Peroxide Cured – No Zinc.  
**Reinforcement:** Synthetic, high tensile textile cord.  
**Cover:** Type P (EPDM), Black with orange stripe. Wrapped appearance.  
**Design Factor:** 4:1

**COUPLINGS:** 75 Gates GLX® or 82 Gates SS. Reference the Hose Coupling Section.

**STANDARDS:** **Tube:** Zinc and Calcium Carbonate Free.