

## Material Handling Hose

### Bulk Master™ Sand Blast (120-150) D Formerly - 429W



Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)			(ft)		
Black	1/2	12.7	150	25.0	5.0	.55	50	PLT	T	Stock	4129-0085	\$11.46
Black	3/4	19.1	150	15.0	8.0	.70	50	PLT	T	Stock	4129-0086	15.00
Black	1	25.4	150	5.0	12.0	.70	50	PLT	T	Stock	4129-0256	18.53
Black	1	25.4	150	5.0	12.0	.96	50	PLT	T	Stock	4129-0100	21.09
Black	1 1/4	31.8	150	5.0	12.0	1.12	50	PLT	T	Stock	4129-0105	25.32
Black	1 1/2	38.1	135	5.0	18.0	1.56	50	PLT	T	Stock	4129-0150	28.20
Black	2	50.8	120	5.0	20.0	2.00	50	PLT	T	Stock	4129-0200	35.72

**RECOMMENDED FOR:** Sand, shot-blasting work and wherever abrasive materials are carried at high velocity.

**TEMPERATURE:** -40°F to +150°F (-40°C to +66°C) continuous service.

**CONSTRUCTION:** **Tube:** Type D3 (Natural Rubber). Black. Static-conductive.  
**Reinforcement:** Synthetic, high tensile textile.  
**Cover:** Type D (SBR). Black with gray stripe. All sizes are perforated.  
**Design Factor:** 4:1

**COUPLINGS:** 36. Reference the Hose Coupling Section.

AGRICULTURE
AIR BREATHING
AIR DUCT
AIR AND MULTI-PURPOSE
CHEMICAL
FOOD AND BEVERAGE
MARINE AND ENGINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM
PRESSURE WASH AND WASHDOWN
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE