

## Petroleum Hose

### LP350

Formerly - LP350, LP350X



#### LP350

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)					
Black	1/4	.58	350	30.0	3.0	.14	700	Reel	EE	Stock	3220-1200	\$4.49
Black	1/4	.58	350	30.0	3.0	.14	3700	PLT	Y	MTO	3220-1201	4.04
Black	3/8	.74	350	30.0	3.0	.21	700	Reel	EE	Stock	3220-1202	5.81
Black	3/8	.74	350	30.0	3.0	.21	2000	PLT	Y	MTO	3220-1203	5.22
Black	1/2	.91	350	25.0	5.0	.28	700	Reel	EE	Stock	3220-1204	7.79
Black	1/2	.91	350	25.0	5.0	.28	1000	PLT	SS	Stock	3220-1205	7.01
Black	3/4	1.23	350	20.0	6.0	.44	100	Ctn	T	Stock	3220-1207	15.02
Black	3/4	1.23	350	20.0	6.0	.44	125	Ctn	T	Stock	3220-1208	15.02
Black	3/4	1.23	350	20.0	6.0	.44	150	Ctn	T	Stock	3220-1209	15.02
Black	3/4	1.23	350	20.0	6.0	.44	350	Reel	KK	Stock	3220-1206	13.07
Black	1	1.51	350	15.0	8.0	.66	100	Ctn	T	Stock	3220-1211	18.89
Black	1	1.51	350	15.0	8.0	.60	125	Ctn	T	Stock	3220-1212	18.89
Black	1	1.51	350	15.0	8.0	.60	150	Ctn	T	Stock	3220-1213	18.89
Black	1	1.51	350	15.0	15.0	.63	200	Ctn	T	MTO	3220-1216	18.89
Black	1	1.51	350	15.0	8.0	.60	350	Reel	KK	Stock	3220-1210	16.43
Black	1 1/4	1.85	350	10.0	10.0	.98	300	Reel	G	Stock	3220-0855	32.69
Black	1 1/2	2.25	350	10.0	12.0	1.26	60	Ctn	T	Stock	3320-0935	41.67
Black	2	2.86	350	10.0	14.0	1.84	50	Ctn	T	MTO	3320-0939	53.10
Black	2	2.86	350	10.0	14.0	1.81	60	Ctn	T	Stock	3320-0938	53.10
Black	3	3.88	350	10.0	24.0	2.58	60	Ctn	T	Stock	3320-0934	89.57

#### LP350 Power Crimp® Ferrules

Size (in)	Wt. Per ea (Lbs.)	Std. Pack	Pkg Code	Stock or MTO (ea)	Gates Item No.	List Price Per ea
3/4	.21	Bulk	150	Stock	7266-0735	\$13.80
3/4	.21	Bulk	1	Stock	7266-07355	13.80
1 1/2	.80	Bulk	20	Stock	7266-0734	91.10
1 1/2	.80	Bulk	1	Stock	7266-07345	91.10
2	1.72	Bulk	12	Stock	7266-0733	114.95
2	1.72	Bulk	1	Stock	7266-07335	114.95

NOTE: These ferrules are to be used with LP350 hose only.

**RECOMMENDED FOR:** Liquid or gaseous propane, butane or any combination of these two mixtures. Can be used for natural gas (not to exceed 50 psi) under certain conditions such as: open/outside areas and well ventilated factory buildings (if local building codes permit).

**CAUTION:** Not recommended for residential, office buildings or as fuel line hose on compressed natural gas vehicles. Contact Denver Product Application (303) 744-5070 for inspection and assembly testing information.

**TEMPERATURE:** -40°F to +180°F (-40°C to +82°C) continuous service. Warning: Do not convey LP Gas over +140°F (60°C).

**CONSTRUCTION:** **Tube:** Type A (Chloroprene). Black. 1 1/2" - 3".  
Type C (Nitrile). Black. 1/4" - 1 1/4".  
**Reinforcement:** Braided, synthetic high tensile cord. 1 1/4" - 3".  
High tensile synthetic textile cord. 1/4" - 1".  
**Cover:** Type A (Chloroprene). Black. All sizes are perforated.  
**Design Factor:** 5:1

**COUPLINGS:** 72 Gates Power Crimp® for 3/4", 1 1/2" and 2" I.D. or 75 Gates GLX® sizes 1/4" to 1 1/4". For Power Crimp® ferrules, reference the Hose Coupling Section. Do not use male swivel, reusable or O-ring type couplings. For 3" I.D. use Dixon LP Boss only.

**STANDARDS:** CAN/CGA-8.1-M86.  
NFPA 58, Section 8-3.5.  
Underwriters Laboratories Standard No. 21. (Applies to all sizes).