

## Steam Hose

### Plant Master® Steam 250 Formerly - 205MB Steam King®



#### Smooth Cover

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO (ft)	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)					
Black	3/8	9.5	250	30.0	4.0	.26	50	Bulk	250	Stock	3605-0650	\$7.92
Black	3/8	9.5	250	30.0	4.0	.26	250	Reel	LL	Stock	3605-0652	7.92
Black	1/2	12.7	250	25.0	7.0	.40	50	Bulk	200	Stock	3605-0655	9.65
Black	1/2	12.7	250	25.0	7.0	.40	50	Bulk	1500	Stock	3605-0677	9.15
Black	1/2	12.7	250	25.0	7.0	.40	500	Reel	VV	Stock	3605-0672	9.65
Black	3/4	19.1	250	20.0	9.0	.49	50	Bulk	150	Stock	3605-0664	11.22
Black	3/4	19.1	250	20.0	9.0	.49	50	Bulk	1000	Stock	3605-0679	10.67
Black	3/4	19.1	250	20.0	9.0	.49	500	Reel	VV	Stock	3605-0678	11.22
Black	1	25.4	250	20.0	11.0	.78	500	Reel	VV	Stock	3605-0668	16.28

#### Wrapped Cover

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO (ft)	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)					
Black	3/4	19.1	250	20.0	9.0	.57	50	Bulk	100	Stock	3605-0901	\$11.22
Black	1	25.4	250	20.0	11.0	.70	50	Bulk	200	Stock	3605-0665	16.28
Black	1	25.4	250	20.0	11.0	.70	50	Bulk	600	Stock	3605-0669	15.51
Black	1 1/4	31.8	250	20.0	16.0	.90	50	Ctn	T	Stock	3605-0671	23.42
Black	1 1/2	38.1	250	10.0	20.0	1.21	50	Ctn	T	Stock	3605-0676	29.52
Black	2	50.8	250	10.0	25.0	1.57	50	Ctn	T	Stock	3605-0681	35.31

#### Assemblies - Wrapped Cover

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ea	Length	Std. Pack	Pkg Code	Stock or MTO (ea)	Gates Item No.	List Price Per ea
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ea)					
Black	3/4	19.1	250	20.0	9.0	31.90	50 ft. F/F	Assy	T	Stock	3605-0736	\$642.05
Black	3/4	19.1	250	20.0	9.0	30.90	50 ft. F/M	Assy	T	Stock	3605-0737	603.36
Black	3/4	19.1	250	20.0	9.0	29.90	50 ft. M/M	Assy	T	Stock	3605-0738	564.66

**RECOMMENDED FOR:** All types of steam – saturated and superheated – up to 250 PSI and +450°F (+232°C).

**CAUTION:** Do not alternate use between steam and water.

**TEMPERATURE:** -40°F to +450°F (-40°C to +232°C) continuous service.

**CONSTRUCTION:**  
**Tube:** Type P2 (EPDM). Black.  
**Reinforcement:** Braided, high tensile steel wire.  
**Cover:** Type P2 (EPDM). Black with red stripe. All sizes are perforated.  
**Design Factor:** 10:1

**COUPLINGS:** 14, 15 or 76 only. Reference the Hose Coupling Section.