

## Water Hose

### Water Master® Plus PVC Layflat (100-150) D



Color	Hose I.D.	Hose O.D.	Max. W.P.*	Vac.*	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)	(mm)	(psi)	(In. Hg)	(in)	(Lbs.)	(ft)			(ft)		
Red	1 1/2	38.1	150	—	—	.23	300	PLT	T	Stock	7744-1538	\$3.29
Red	2	50.8	150	—	—	.36	300	PLT	T	Stock	7744-1539	4.87
Red	2 1/2	63.5	150	—	—	.41	300	PLT	T	Stock	7744-1540	6.18
Red	3	76.2	125	—	—	.46	300	PLT	T	Stock	7744-1541	6.24
Red	4	101.6	100	—	—	.73	300	PLT	T	Stock	7744-1542	8.56
Red	6	152.4	100	—	—	1.18	300	PLT	T	Stock	7744-1543	18.22

NOTE: \* Working Pressure and Vacuum at +72°F (+22°C).

**RECOMMENDED FOR:** For medium-duty discharge applications in mining, construction, industrial, agriculture and marine service. Limited oil and chemical application.

**TEMPERATURE:** -10°F to +150°F (-23°C to +66°C) continuous service.

**CONSTRUCTION:**  
**Tube:** Type G (PVC). Black.  
**Reinforcement:** Spiral synthetic yarn, one layer longitudinal synthetic yarn.  
**Cover:** Type G (PVC). Red.  
**Design Factor:** 3:1

**COUPLINGS:** 5, 6, 7, 49 or 84. Reference the Hose Coupling Section.

AGRICULTURE
AIR BREATHING
AIR DUCT
AIR AND MULTI-PURPOSE
CHEMICAL
FOOD AND BEVERAGE
MARINE AND ENGINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM
PRESSURE WASH AND WASHDOWN
STEAM
<b>WATER</b>
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE