




17 - SAE 61系列-法兰式45°弯接头

ISO 12151-3 – E45 – L / SFL 45° / 3000 psi



适用软管类型:



| XXXX-XX-XX 型号  |  软管内径 | | | |  法兰规格 | A | B | E | F |
|---|--|-------|------|------|---|-----|-----|----|----|
| | DN | Inch | Size | mm | | mm | mm | mm | mm |
| 11770-8-8 | 12 | 1/2 | -8 | 12,7 | 1/2 | 79 | 44 | 20 | 30 |
| 11770-10-10 | 16 | 5/8 | -10 | 15,9 | 5/8 | 104 | 67 | 24 | 34 |
| 11770-12-10 | 16 | 5/8 | -10 | 15,9 | 3/4 | 96 | 57 | 26 | 38 |
| 11770-12-12 | 20 | 3/4 | -12 | 19,1 | 3/4 | 98 | 58 | 26 | 38 |
| 11770-16-12 | 20 | 3/4 | -12 | 19,1 | 1 | 97 | 57 | 25 | 45 |
| 11770-16-16 | 25 | 1 | -16 | 25,4 | 1 | 119 | 74 | 32 | 45 |
| 11770-20-16 | 25 | 1 | -16 | 25,4 | 1-1/4 | 121 | 76 | 32 | 51 |
| 11770-20-20 | 32 | 1-1/4 | -20 | 31,8 | 1-1/4 | 132 | 85 | 29 | 51 |
| 11770-24-20 | 32 | 1-1/4 | -20 | 31,8 | 1-1/2 | 141 | 94 | 38 | 60 |
| 11770-24-24 | 40 | 1-1/2 | -24 | 38,1 | 1-1/2 | 166 | 106 | 37 | 60 |
| 11770-32-24 | 40 | 1-1/2 | -24 | 38,1 | 2 | 165 | 105 | 37 | 71 |

配套的法兰见样本E部分
 正常订货情况下配丁晴橡胶O型圈的接头可在-30°C~+105°C温度下正常使用，如有需要，可订购其他特殊材料的O型圈。
 O型圈的尺寸和型号请参考样本E栏中O型圈部分。
 材料: 碳钢, 镀锌

D