Hose Type 8/6H



Applications

Waterblasting: Ultra High Pressure Waterjet Table Cutting, Surface Preparation, Paint Removal, Tank & Vessel Cleaning, Hydro Demolition of Concrete, Robotic Surface Cleaning of Ships,

Automated Cleaning Booths

Hydraulics: Pressure Testing for Valves, Tooling and Control

Panels

Inner Core: Polyoxymethylene (POM)

Pressure Support: 6 layers of high-tensile steel wire

Outer Cover: Polyamide (PA)

Colour: red, other colours upon request -22°F to 140°F [-30°C to +60°C] Temperature:



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,30 inch	0,74 inch	36.250 psi	90.620 psi	10,24 inch	0,622 lbs/ft	0,18 inch	10860122 carbon steel	1,01 inch
7,7 mm	18,8 mm	2.500 bar	6.250 bar	260 mm	0,925 kg/m	4,5 mm		25,7 mm

Fittings: ID8, Series C

Description	Size	Material	Part Number		
HP fitting	3/8"x24 UNF LH	stainless steel	40860214C	H	
HP fitting	9/16"x18 UNF LH	stainless steel	40860204C		
HP fitting	M14x1.5 LH	stainless steel	40860104C		
MP fitting	3/4"x16 UNF LH	stainless steel	40860324C		
metric female swivel with O-Ring	M24x1.5	stainless steel AISI 316Ti carbon steel	20860224C swivel nut / 51360205 swivel nut / 51360201	D-Ring	
Type M female swivel	3/4"x16 UNF	stainless steel AISI 316 Ti carbon steel	20860644C swivel nut / 50840605 swivel nut / 50840601		
Type M female swivel	7/8"x14 UNF	stainless steel AISI 316 Ti	20860684C swivel nut / 50860675		

---- Additional fittings are available upon request. ----

