Hose Type 13/2



Applications

Waterblasting: Paint Removal, Tank & Vessel Cleaning, Automated Cleaning Booths, Waterblast Supply Hose, Large Bore

Tube Cleaning

Hydraulics: Pressure Testing for Valves, Tooling and Control

Panels

Oil and Gas: Grease Injection

Inner Core: Polyamide (PA)

2 layers of high-tensile steel wire **Pressure Support:**

Outer Cover: Polyamide (PA)

Colour: green, other colours upon request -22°F to 140°F [-30°C to +60°C] Temperature:



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,51 inch	0,76 inch	10.000 psi	25.010 psi	7,87 inch	0,292 lbs/ft	0,33 inch	11320101	1,02 inch
12,9 mm	19,3 mm	690 bar	1.725 bar	200 mm	0,435 kg/m	8,5 mm	carbon steel	26,0 mm

Fittings: ID13, Series A

Description	Size	Material	Part Number		
male fitting	1/2"x14 NPTF	carbon steel	31320401A	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
BSP female swivel	G1/2"	carbon steel carbon steel AISI 316Ti	21320311A swivel nut / 51060311 swivel nut / 51060315	70 p.,	
metric female swivel with O-Ring	M22x1.5	carbon steel	21320101A / 51360221	U-Ring	
metric female swivel with O-Ring	M24x1.5	carbon steel carbon steel AISI 316Ti	21320241A swivel nut / 51360201 swivel nut / 51360205		
Type M female swivel	1"x12 UNF	carbon steel	21320641A / 51360641		
Type M female swivel	1"x12 UNF	AISI 316Ti AISI 316Ti AISI 303	21320645A swivel nut / 51360645 swivel nut / 51360643		

---- Additional fittings are available upon request. ----

