## **Hose Type 6/4PPA**



## **Applications**

Oil and Gas: Chemical Injection, Gaseous Media Handling, Hydraulic Control, Methanol Injection, Nitrogen Service, Sub Sea

Well Control

**PVDF** Inner Core:

Pressure Support: 4 layers of high-tensile steel wire

Outer Cover: Polyamide (PA)

dark green, other colours upon request Colour:

Temperature: -4°F to 176°F [-20°C to +80°C]



ØID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,25 ir	ch 0,50 inch	17.110 psi	60.030 psi	11,02 inch	0,205 lbs/ft	0,14 inch	10640101 carbon steel	0,65 inch
6,3m	n 12,6 mm	1.180 bar	4.140 bar	280 mm	0,305 kg/m	3,5 mm	10640105 AISI 316Ti	16,4 mm

## Fittings: ID6, Series B and Y

Description	Size	Material	Part Number		
HP fitting	3/8"x24 UNF LH	AISI 316Ti	40640205B	3	
HP fitting BLAST PRO <sup>2</sup> )	3/8"x24 UNF LH	stainless steel carbon steel	40640214Y sleeve / 10640232		
HP female BLAST PRO <sup>2</sup> )	3/8"x24 UNF	stainless steel carbon steel	40640234Y sleeve / 10640232	Fendle BLAST PRD waterplast fitting	
male fitting	1/4"x18 NPTF	2x18 NPTF carbon steel 30640		000	
male fitting with 60° cone	G1/4"	carbon steel	30640301B	\$	
BSP female swivel	G1/4"	carbon steel carbon steel AISI 316 Ti	20640301B swivel nut / 50540301 swivel nut / 50540305	Z. S. M. S.	
metric female swivel with O-Ring	M18x1.5	carbon steel	20640241B / 50620201	X O-Ring	
Type M female swivel	9/16"x18 UNF	carbon steel	20640641B / 50540601		
Type M female swivel	9/16"x18 UNF	AISI 316Ti	20640645B / 50540605		
JIC female swivel	9/16"x18 UNF	AISI 316Ti	20640655B / 50540605	* P	

---- Additional fittings are available upon request. ----

