

Hose Type 13/4HPPA



Applications

Oil and Gas : Chemical Injection, Gaseous Media Handling, Hydraulic Control, Methanol Injection, Nitrogen Service, Sub Sea Well Control

Inner Core : **PVDF**
 Pressure Support : **4 layers of high-tensile steel wire**
 Outer Cover : **Polyamide (PA)**
 Colour : **dark green, other colours upon request**
 Temperature : **-4°F to 176°F [-20°C to +80°C]**



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹⁾)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,50 inch	0,87 inch	15.080 psi	52.490 psi	11,81 inch	0,672 lbs/ft	0,30 inch	11340232 carbon steel	1,16 inch
12,8mm	22,0 mm	1.040 bar	3.620 bar	300 mm	1,000 kg/m	7,5 mm		29,5 mm

Fittings : ID13, Series C

Description	Size	Material	Part Number	
HP fitting	9/16"x18 UNF LH	stainless steel	41360214C	
MP fitting	3/4"x16 UNF LH	stainless steel	41360204C	
BSP female swivel	G1/2"	stainless steel AISI 316Ti carbon steel	21360314C swivel nut / 51060315 swivel nut / 51060311	
metric female swivel with O-Ring	M24x1.5	stainless steel AISI 316Ti carbon steel	21360244C swivel nut / 51360205 swivel nut / 51360201	
Type M female swivel	1"x12 UNF	stainless steel AISI 316Ti carbon steel AISI 303	21360644C swivel nut / 51360645 swivel nut / 51360641 swivel nut / 51360643	

----- Additional fittings are available upon request. -----

¹⁾Production related variations up to 5 % are possible

^{*)} The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR[®] assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

