

CASCADE

INDUSTRIAL MAINTENANCE

Water/Cleaning and wash-down



Applications

Water discharge under pressure on industrial or urban sites and all water discharge applications in building and public works.

Advantages

- Extremely resistant to ageing and atmospheric conditions.
- Highly flexible and easy-to-hold due to the fluted cover.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, green, fluted.

Temperature range: - 30 °C to + 70 °C.

Standard/Approval: in compliance with NF EN ISO 1403 type 2 (except branding).

| ID | | Wall thickness | OD | | Working pressure | Bursting pressure | Bending radius | Weight | Length | Notes |
|-------------|-------|----------------|------|-------|------------------|-------------------|----------------|--------|---------------------|-------|
| mm | | mm | mm | | bar | bar | mm | kg/m | m | |
| 12.7 | ± 0.6 | 4.0 | 20.7 | ± 0.7 | 10 | 30 | 70 | 0.28 | 40 | |
| 15.8 | ± 0.7 | 4.1 | 24.0 | ± 0.8 | 10 | 30 | 80 | 0.34 | 20 - 40 - 80 | |
| 19.4 | ± 0.7 | 4.5 | 28.4 | ± 0.8 | 10 | 30 | 120 | 0.45 | 20 - 40 - 80 | |
| 25.4 | ± 1.0 | 4.8 | 35.0 | ± 1.1 | 10 | 30 | 150 | 0.60 | 20 - 40 | |

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

