

VULPANE

INDUSTRIAL MAINTENANCE

Gas and welding



Applications

Rubber hose for LPG (gas cylinders, heaters, welding, and LPG lines).

Advantages

- Flexible and light weight for easy handling.
- Long, safe service life.
- A hose cover particularly resistant to atmospheric conditions (ozone and hot spots).
- Special, high quality rubber compounds.
- Very strong textile reinforcement giving high safety factor.
- Clear branding showing gas symbol and date of manufacture.

Technical description

Inner tube: NBR/SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, orange, smooth.

Temperature range: - 30 °C to + 80 °C.

Standard/Approval: EN 559, ISO 3821, DG 3910.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes	
6.3	± 0.5	2.85	12.0	± 0.6	20	60	55	0.12	20 - 40 - 100 - 120
8.0	± 0.5	3.00	14.0	± 0.6	20	60	65	0.15	20 - 40 - 50 - 60 - 80 - 100 - 120
9.0	± 0.5	3.00	15.0	± 0.6	20	60	70	0.18	40 - 120
10.0	± 0.5	3.50	17.0	± 0.6	20	60	75	0.20	20 - 25 - 40 - 100 - 120
19.0	± 0.6	3.75	26.5	± 0.8	20	60	130	0.37	40

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding: