

SOLVYKLER

INDUSTRIAL MAINTENANCE

Solvents/Paints/Lacquer and varnish



Applications

Pressure service line for ester, ketone, alcohol based paints, and numerous chemicals.

Advantages

- Hose cover resistant to splashing of corrosive chemicals.
- Free from silicone.
- Hose remains flexible within a wide temperature range.
- Antistatic tube.

Technical description

Inner tube: chemical resistant EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: chemical and weather resistant EPDM, green, smooth.

Temperature range: - 30 °C to + 100 °C.

Electrical properties: antistatic tube, $R < 10^6 \Omega/m$.

Couplings/Fittings

Special paint hose couplings are recommended.

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Notes	
mm	mm	mm	bar	bar	mm	kg/m	m		
6.0	± 0.4	3.3	12.6	± 0.5	20	60	60	0.13	40 - 80 - 120
8.0	± 0.5	3.5	15.0	± 0.6	20	60	70	0.16	40 - 80 - 120
9.0	± 0.5	3.5	16.0	± 0.6	20	60	85	0.17	40 - 80 - 120
10.0	± 0.5	4.0	18.0	± 0.6	20	60	90	0.22	40 - 80 - 120
13.0	± 0.6	4.0	21.0	± 0.7	20	60	110	0.27	40 - 80 - 120
16.0	± 0.8	4.0	24.0	± 1.0	20	60	130	0.32	40 - 80
20.0	± 0.8	4.5	29.0	± 1.0	20	60	150	0.44	40 - 80
25.0	± 1.2	4.5	34.0	± 1.5	20	60	170	0.54	40 - 80

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:



TRELLEBORG

SOLVYKLER - Made in France