

MULTIKLER

INDUSTRIAL MAINTENANCE

Solvents/Paints/Lacquer and varnish



Applications

Pressure service line for benzene, toluene, and xylene based paints, lacquer, varnish, and certain chemicals.

Also for industrial paint spray equipment.

Advantages

- Hose cover resistant both to abrasion and to corrosive chemicals.
- Free from silicone.
- Antistatic tube.

Technical description

Inner tube: solvent paints resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, green, smooth.

Temperature range: - 20 °C to + 100 °C.

Electrical properties: antistatic tube, $R < 10^8 \Omega/m$.

Couplings/Fittings

Special paint hose couplings are recommended.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes	
6.0	± 0.4	3.3	12.6	± 0.5	20	60	60	0.14	40 - 80 - 120
8.0	± 0.5	3.5	15.0	± 0.6	20	60	70	0.17	40 - 80 - 120
10.0	± 0.5	3.75	17.5	± 0.6	20	60	90	0.24	20 - 40 - 80 - 120
13.0	± 0.6	4.0	21.0	± 0.7	20	60	110	0.28	40 - 80 - 120
16.0	± 0.7	4.5	25.0	± 0.8	20	60	130	0.38	40 - 80 - 120

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

