

BOAT SANITARY HOSE

VEHICLE

Water/Special applications



Applications

Effluent hose for leisure boat toilet systems.

Advantages

- Flexible.
- Kink resistant.
- Diffusion tight (will not be tainted by odour from the toilet system).
- Easy cut and crush-proof due to plastic helix.

Technical description

Inner tube: diffusion tight butyl rubber, black.

Reinforcement: synthetic textile with embedded PET helix.

Cover: EPDM, grey, fabric impression.

Temperature range: - 30 °C to + 100 °C.

ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
16.0	5.25	± 0.75	27.0	± 1.00	10	32	0.8	60	0.55	40	
20.0	5.25	± 0.75	31.0	± 1.00	10	32	0.8	80	0.63	20 - 40	
25.0	5.25	± 0.75	36.0	± 1.00	10	32	0.8	100	0.74	20 - 40	
38.0	5.25	± 0.75	49.0	± 1.00	10	32	0.8	160	1.05	20 - 40	

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

BOAT SANITARY HOSE

Made in France



TRELLEBORG