

PUMPADUKT D

CHEMICAL AND PETROCHEMICAL

Oil and petroleum/Discharge applications



Applications

Discharge of petroleum products, especially designed for applications on reels.
Road tanker equipment for oil delivery (aromatic content up to 50 %).

Advantages

- Hose can be cut to length as required.
- Cover especially designed for oil, abrasion and weather resistance.
- Electrical conductivity ensured by the tube compound.
- In compliance with chemicals industry requirements.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant CR, black, fabric impression.

Temperature range: - 40 °C to + 100 °C .

Electrical properties: conductive tube and cover, $R < 10^6 \Omega/\text{lg}$.

Standard/Approval: EN 1761, EN 12115.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
19.0	6.0 ± 0.5	31.0 ± 1.0	16	64	125	0.65	20 - 40	
25.0	6.0 ± 0.5	37.0 ± 1.0	16	64	150	0.78	20 - 40	
32.0	6.0 ± 0.5	44.0 ± 1.0	16	64	175	0.92	20 - 30 - 40 - 50 - 60 - 80	
38.0	6.5 ± 0.5	51.0 ± 1.0	16	64	225	1.20	20 - 30 - 40 - 50 - 60 - 80	
40.0	7.0 ± 0.6	54.0 ± 1.0	16	64	240	1.35	20 - 40	
50.0	8.0 -0.6/+ 0.8	66.0 ± 1.2	16	64	275	1.88	20 - 40	
63.0	8.0 -0.6/+ 0.8	79.0 ± 1.5	16	64	300	2.40	20 - 40	
65.0	8.0 -0.6/+ 0.8	81.0 ± 1.5	16	64	310	2.45	20 - 40	
75.0	8.0 -0.6/+ 0.8	91.0 ± 1.5	16	64	350	2.89	20 - 40	
80.0	8.0 -0.6/+ 0.8	96.0 ± 1.5	16	64	375	3.02	20 - 40	
100.0	8.0 -0.6/+ 0.8	116.0 ± 1.5	16	64	450	3.60	20 - 40	

Length in orange = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

PUMPADUKT D



TRELLEBORG

and embossed: TRELLEBORG - PUMPADUKT D - NBR1 - EN 1761 - EN 12115 - ND - D - PN 16 - month/year