

TRELLVAC Handler HD

CONSTRUCTION AND ENVIRONMENT

Evacuation and material handling hoses



Applications

Heavy duty working hose on vacuum cleaning trucks for use at the work site.

Advantages

- Light and flexible with good wear resistance.
- TRELLVAC Handler HD is a working hose for heavy materials when wear resistance is of highest priority.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile, woven fabric with embedded steel helix.

Cover: wear and weather resistant SBR/NR, black, corrugated.


Temperature range: - 30 °C to + 90 °C.

Electrical properties: non conductive. The helix can be connected to couplings in both ends, Built-in conductive wire.

Complementary information

OD measured on top of corrugation.

Resistance



Flexibility



Weight



ID	OD		Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Notes
mm	mm		bar	bar	bar	mm	kg/m	m	
102.0	118	± 1.6	5	15	0.9	400	3.1	20 - 40	
127.0	143	± 1.6	5	15	0.9	500	3.8	20 - 40	
152.0	168	± 2.0	5	15	0.9	600	4.55	20	
204.0	225	± 2.0	1.5	4.5	0.9	800	8.2	12	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLVAC Handler HD



TRELLEBORG