

SUPERVRAC AL

CONSTRUCTION AND ENVIRONMENT

Bulk tank truck discharge

SUPERVRAC AL



FDA



Applications

Pneumatic transport of bulk abrasive products for the food industry.
Discharge from road and rail tankers, and delivery to storage bins: foodstuffs and chemicals (fertilizers, granulates, PVC, dye stuffs, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.

Technical description

Inner tube: foodgrade, wear resistant NR, white, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: - 30 °C to + 80 °C.

Electrical properties: non conductive and built-in conductive wire.

Standard/Approval:

FDA regulation 21 CFR 177.2600.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Notes	
89.0	6.00	± 1.00	101.0	± 1.5	7	21	2.07	20 - 40
100.0	9.00	± 1.25	118.0	± 1.5	7	21	3.60	40
110.0	6.50	± 1.25	123.0	± 1.5	7	21	2.63	20 - 40

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

SUPERVRAC AL



FDA



TRELLEBORG