



BOAT SANITARY HOSE

CONSTRUCTION & MINING EQUIPMENT

Water/Special applications

Effluent hose for leisure boat toilet systems.

Advantages

- Flexible.
- Kink resistant.
- Diffusion tight (will not be tainted by odour from the toilet system).
- Easy cut and crush-proof due to plastic helix.

Technical description

Inner tube: diffusion tight butyl rubber, black.

Reinforcement: synthetic textile with embedded PET helix.

Cover: EPDM, grey, fabric impression.

Temperature range: -30°C to +100°C.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
16.0	5.25 ±0.75	27.0 ±1.00	10	32	0.8	60	0.55	40	
20.0	5.25 ±0.75	31.0 ±1.00	10	32	0.8	80	0.63	20 - 40	
25.0	5.25 ±0.75	36.0 ±1.00	10	32	0.8	100	0.74	20 - 40	
38.0	5.25 ±0.75	49.0 ±1.00	10	32	0.8	160	1.05	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

