



ZEPHIR S

CONSTRUCTION & MINING EQUIPMENT

Evacuation and material handling hoses

For suction of light industrial debris and dust.
Suitable for conveying small particles and moderately abrasive materials.

Advantages

- Very light weight and easy to handle.
- Excellent bending radius and flexibility.
- Very good crush resistance.

Technical description

Inner tube: wear resistant NR, beige, smooth.
Reinforcement: synthetic textile, cords, with embedded steel helix.
Cover: rubber coated fabric, white, corrugated.
Temperature range: -30°C to +70°C.



ID mm	Wall thickness mm	OD mm	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
30.0	±1.5	4.5 ±0.75	39.0 ±1.5	0.8	150	0.50	10
35.0	±1.5	4.5 ±0.75	44.0 ±1.5	0.8	175	0.57	10
40.0	±1.5	4.5 ±0.75	49.0 ±1.5	0.8	200	0.63	10
50.0	±1.5	4.5 ±1.0	59.0 ±2.0	0.8	250	0.79	10
60.0	±1.5	4.5 ±1.0	69.0 ±2.0	0.8	300	0.90	10
70.0	±1.5	4.5 ±1.0	79.0 ±2.0	0.8	350	1.02	10
80.0	±1.5	5.5 ±1.0	91.0 ±2.0	0.8	400	1.46	10
100.0	±1.5	5.5 ±1.0	111.0 ±2.0	0.8	500	1.79	10
105.0	±1.5	5.5 ±1.0	116.0 ±2.0	0.8	525	1.84	10
115.0	±1.5	5.5 ±1.0	126.0 ±2.0	0.8	575	2.00	10
125.0	±1.5	5.5 ±1.0	136.0 ±2.0	0.8	625	2.23	10
150.0	±1.5	7.0 ±1.0	164.0 ±2.0	0.8	750	3.76	10

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

No branding