



TRELLVAC Handler LD

CONSTRUCTION & MINING EQUIPMENT

Evacuation and material handling hoses

For industrial vacuum cleaners and cleaning systems.
Useful for suction of drainage sludge, sand, etc.

Advantages

- Light and flexible design.
- Very good wear resistance.
- Especially useful when low weight and easy handling are valued.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: wear and weather resistant SBR, black, corrugated.

Temperature range: -30°C to +80°C.

Electrical properties: non conductive. The helix can be connected to couplings in both ends

Complementary information

OD measured on top of corrugation.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
51.0	61.0 ±1.5	5	15	0.9	85	1.00	20 - 40	
60.0	70.0 ±1.5	5	15	0.9	105	1.15	20 - 40	
63.0	73.0 ±1.5	5	15	0.9	110	1.22	20 - 40	
76.0	86.5 ±1.5	5	15	0.9	135	1.50	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

