



SABLEX

CONSTRUCTION & MINING EQUIPMENT

Blasting and guniting

For cleaning and shot blasting castings, metal, stone and concrete surfaces.

Advantages

- Small tolerances, therefore easy to couple.
- Longitudinally stable i.e. the length will not alter under pressure (unstable hoses result in the operator losing control when pressure is applied).
- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30°C to +70°C.

Electrical properties: conductive tube, $R < 2.10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70mm^3$ according to ISO 4649.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
13.0	7.0 ±0.50	27.0 ±1.0	12	40	65	0.58	40	
16.0	7.0 ±0.50	30.0 ±1.0	12	40	80	0.68	20 - 40	
19.0	7.5 ±0.50	34.0 ±1.0	12	40	100	0.78	20 - 40	
25.0	7.0 ±0.50	39.0 ±1.0	12	40	125	0.86	20 - 40	
32.0	8.0 ±0.50	48.0 ±1.0	12	40	160	1.30	20 - 40	
32.0	11.0 ±0.50	54.0 ±1.0	12	40	140	1.85	20 - 40	
35.0	9.0 ±0.50	53.0 ±1.0	12	40	190	1.57	40	
38.0	10.0 ±0.50	58.0 ±1.0	12	40	170	1.89	20 - 40	
40.0	10.0 ±0.50	60.0 ±1.0	12	40	180	1.97	20 - 40	
42.0	9.0 ±0.50	60.0 ±1.0	12	40	240	1.81	20 - 40	
50.0	10.0 ±0.75	70.0 ±1.5	12	40	250	2.36	40	
63.0	10.0 ±0.75	83.0 ±1.5	12	40	325	2.90	40	
65.0	10.0 ±0.75	85.0 ±1.5	12	40	320	2.95	20 - 40	
76.0	10.0 ±0.75	96.0 ±1.5	12	40	400	3.42	40	
102.0	10.0 ±0.75	122.0 ±1.5	10	40	550	4.40	40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

