



# TRELLBLAST S

## CONSTRUCTION & MINING EQUIPMENT

### Blasting and guniting

For cleaning and shot blasting castings, metal, stone and concrete surfaces.

### Advantages

- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** wear and weather resistant SBR, black, fabric impression.

**Temperature range:** -30°C to +70°C.

**Electrical properties:** conductive tube,  $R < 2 \cdot 10^6 \Omega/m$ .

**Special properties:** abrasion resistance of tube  $< 70 mm^3$  according to ISO 4649.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
<b>13.0</b>	7.0 ±0.5	27.0 ±1	10	30	65	0.56	<b>40</b>	
<b>16.0</b>	7.0 ±0.5	30.0 ±1	10	30	80	0.68	40	
<b>19.0</b>	7.5 ±0.5	34.0 ±1	10	30	100	0.74	<b>40</b>	
<b>25.0</b>	7.0 ±0.5	39.0 ±1	10	30	125	0.86	<b>40</b>	
<b>32.0</b>	8.0 ±0.5	48.0 ±1	10	30	160	1.30	<b>40</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

### Branding

