



CASCADE

MANUFACTURING & MACHINE TOOLS

Water/Cleaning and wash-down

Water discharge under pressure on industrial or urban sites and all water discharge applications in building and public works.

Advantages

- Extremely resistant to ageing and atmospheric conditions.
- Highly flexible and easy-to-hold due to the fluted cover.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, green, fluted.

Temperature range: -30°C to +70°C.

Standard/Approval:

in compliance with NF EN ISO 1403 type 2 (except branding).



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
12.7 ±0.6	4.0	20.7 ±0.7	10	30	70	0.28	40	
15.8 ±0.7	4.1	24.0 ±0.8	10	30	80	0.34	20 - 40 - 80	
19.4 ±0.7	4.5	28.4 ±0.8	10	30	120	0.45	20 - 40 - 80	
25.4 ±0.7	4.8	35.0 ±1.1	10	30	150	0.60	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

