



VULCAIN +

MANUFACTURING & MACHINE TOOLS

Air/Compressed air applications

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

Advantages

- Static conductive tube.
- Very flexible hose especially at low temperatures.
- Suitable for hot water.

Technical description

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, blue, smooth.

Temperature range: -40°C to +100°C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
6.0	±0.4	3.0	12.0 ±0.5	20	80	25	0.11	20 - 40 - 120
7.0	±0.4	3.5	14.0 ±0.6	20	80	25	0.15	20 - 40 - 120
8.0	±0.5	3.5	15.0 ±0.6	20	60	30	0.16	20 - 40 - 120
9.0	±0.5	3.5	16.0 ±0.6	20	60	35	0.18	20 - 40 - 120
10.0	±0.5	4.0	18.0 ±0.6	20	60	40	0.23	20 - 40 - 120
12.0	±0.5	4.0	20.0 ±0.7	20	60	60	0.26	20 - 40 - 120

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

