

# MULTIKLER

## MANUFACTURING & MACHINE TOOLS

### Solvents/Paints/Lacquer and varnish

Pressure service line for benzene, toluene and xylene based paints, lacquer, varnish and certain chemicals.  
Also for industrial paint spray equipment.

### Advantages

- Hose cover resistant both to abrasion and to corrosive chemicals.
- Free from silicone.
- Antistatic tube.

### Technical description

**Inner tube:** solvent paints resistant NBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** oil and weather resistant NBR/PVC, green, smooth.

**Temperature range:** -20°C to +100°C.

**Electrical properties:** antistatic tube,  $R < 10^6 \Omega/m$ .

### Couplings/Fittings

Special paint hose couplings are recommended.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes	
<b>6.0</b>	±0.4	3.3	12.6	±0.5	20	60	60	0.14	40 - 80 - 120
<b>8.0</b>	±0.4	3.5	15.0	±0.6	20	60	70	0.17	<b>40</b>
<b>8.0</b>	±0.5	3.5	15.0	±0.6	20	60	70	0.17	80 - <b>120</b>
<b>10.0</b>	±0.5	3.75	17.5	±0.6	20	60	90	0.24	<b>20 - 40 - 80 - 120</b>
<b>13.0</b>	±0.5	4.0	21.0	±0.7	20	60	110	0.28	<b>40 - 80 - 120</b>
<b>16.0</b>	±0.6	4.5	25.0	±0.8	20	60	130	0.38	<b>40 - 80 - 120</b>

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

### Branding

