



SUPERVRAC

MATERIAL HANDLING

Bulk tank truck discharge

Pneumatic transport of bulk abrasive products. Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30°C to +90°C.

Electrical properties: conductive tube and cover, $R < 10^6 \Omega/m$.



ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Notes
75.0	6.75	±1.25	88.5	±2.0	7	21	1.83	20 - 40	
75.0	9.0	±1.00	93.0	±1.5	7	21	2.75	40	
85.0	6.0	±1.00	97.0	±1.5	7	21	2.03	20 - 40	
89.0	6.25	±1.25	101.5	±2.0	7	21	2.07	20 - 40	
100.0	6.0	±1.00	112.0	±1.5	7	21	2.40	20 - 40	
100.0	9.0	±1.00	118.0	±1.5	7	21	3.58	20 - 40	
110.0	6.5	±1.25	123.0	±2.0	7	21	2.71	20 - 40	
127.0	8.5	±1.25	144.0	±2.0	7	21	4.20	20 - 40	
152.0	8.5	±1.25	169.0	±2.0	7	21	5.00	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

