



TRELLOIL D

OIL & GAS

Oil and petroleum/Discharge applications

Multipurpose hose especially designed for petrol, oil and other petrochemical products (with aromatic content up to 50%).

Advantages

- Flexible hose with very good resistance to petroleum products and weather conditions.
- Good cold flexibility.
- Dissipation of static electricity ensured by contact of built-in wire with the coupling.
- Large range of dimensions.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant SBR/NBR, black, fabric impression.

Temperature range: -30°C to +80°C.

Electrical properties: built-in conductive wire



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
30.0	5.5 ±0.5	41.0 ±1.0	10	40	240	0.83	20 - 40	
32.0	5.5 ±0.5	43.0 ±1.0	10	40	250	0.88	20 - 40	
35.0	5.5 ±0.5	46.0 ±1.0	10	40	280	0.94	20 - 40	
38.0	6.0 ±0.7	50.0 ±1.0	10	40	300	1.08	20 - 40	
40.0	7.0 ±0.7	54.0 ±1.0	10	40	320	1.34	20 - 40	
45.0	7.0 ±0.7	59.0 ±1.0	10	40	360	1.46	20 - 40	
50.0	7.0 ±0.7	64.0 ±1.0	10	40	400	1.60	20 - 40	
60.0	7.0 ±0.8	74.0 ±1.5	10	40	480	2.07	20 - 40	
63.0	7.0 ±0.8	77.0 ±1.5	10	40	500	2.15	20 - 40	
70.0	7.5 ±0.8	85.0 ±1.5	10	40	560	2.59	20 - 40	
75.0	7.5 ±0.8	90.0 ±1.5	10	40	600	2.71	20 - 40	
80.0	7.5 ±1.0	95.0 ±1.5	10	40	640	2.81	20 - 40	
85.0	7.5 ±1.0	100.0 ±1.5	10	40	680	3.08	20 - 40	
89.0	8.0 ±1.0	105.0 ±1.5	10	40	710	3.37	20 - 40	
100.0	7.5 ±1.0	115.0 ±1.5	10	40	800	3.46	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

