

# BERGALAV

## PROCESSING EQUIPMENT

### Food industry/Cleaning

For hot water cleaning in food processing plants with possible occasional use with steam up to 160°C.

#### Advantages

- Highly flexible.
- Specially adapted to keep round on reels.
- Contains no phthalate.

#### Technical description

**Inner tube:** food grade quality EPDM, white, smooth.

**Reinforcement:** synthetic textile.

**Cover:** weather resistant EPDM, blue, smooth.

**Temperature range:** -30°C to +160°C.

#### Standard/Approval:

EU regulations n° 1935/2004 and 2023/2006.

FDA regulation 21 CFR 177.2600.

French legislation.

All relevant migrations tests (France and FDA) were performed and confirmed compliant by the French institute of Poitiers (IANESCO).

#### Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
<b>10.0</b> ±0.6	18.0 ±0.7	10	30	75	0.25	<b>20 - 40</b>	
<b>13.0</b> ±0.6	22.0 ±0.7	10	30	95	0.35	<b>20 - 40</b>	
<b>16.0</b> ±0.6	25.0 ±0.8	10	30	110	0.41	<b>20 - 40</b>	
<b>19.0</b> ±0.7	29.0 ±0.9	10	30	135	0.54	<b>20 - 40</b>	
<b>25.0</b> ±0.8	36.0 ±1.0	10	30	180	0.74	<b>20 - 40</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

#### Branding



and embossed: week/year - batch number