

ALIKLER G2

PROCESSING EQUIPMENT

Food industry/Transfer

Suction and discharge of liquid foodstuffs such as wine, beer, milk, oil, fats, cider, fruit juice and alcohol up to 96%.

For unloading bays, processing and filling plants and liquid foodstuff tankers.

Additional air line on road tankers carrying bulk powdered products (not compressor line) at temperatures up to +120°C.

Advantages

- Improved flexibility, very easy to handle.
- A smooth, seamless, white, multipurpose food grade tube that does not propagate bacterial growth.
- Excellent resistance to kinking.
- Changes in temperature have little effect due to the qualities of the rubber compound.
- Resistant to most cleaning processes used in the food industry, either with chemicals (max. 90°C) or steam (max. 130°C). See our users information leaflet.
- Non-marking, abrasion-resistant cover.
- Contains no phthalate.

Technical description

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant NBR/PVC, blue, fabric impression.

Temperature range: -30°C to +100°C.

Standard/Approval:

EU regulations N. 1935/2004 and 2023/2006.

FDA regulation 21 CFR 177.2600.

German legislation: BfR recommendation XXI cat. 2.

French legislation.

All relevant migrations tests (France and FDA) were performed and confirmed compliant by the French institute of Poitiers (IANESCO).

Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
25.0	-0/+1	37.0 ±1.0	10	30	0.9	40	20 - 40	
32.0	-0/+1	44.0 ±1.0	10	30	0.9	55	20 - 40	
38.0	-0/+1	50.0 ±1.0	10	30	0.9	65	20 - 40	
45.0	-0/+1	57.0 ±1.0	10	30	0.9	90	20 - 40	
50.0	-0/+1	62.0 ±1.5	10	30	0.9	100	20 - 40	
50.0	-0/+1	65.0 ±1.5	10	30	0.9	100	20 - 40 *	
53.0	-0/+1	65.0 ±1.5	10	30	0.9	110	20 - 40	
63.0	-0/+1	76.0 ±1.5	10	30	0.9	135	20 - 40	
70.0	-0/+1	84.5 ±1.5	10	30	0.9	175	20 - 40	
75.0	-0/+1	89.5 ±1.5	10	30	0.9	190	20 - 40	
75.0	-0/+1	91.0 ±1.5	10	30	0.9	190	20 - 40 *	
89.0	-0/+1	104.5 ±1.5	10	30	0.9	275	20 - 40	
100.0	-0/+1	115.5 ±1.5	10	30	0.9	400	20 - 40	
125.0	-0/+1	145.5 ±2.0	10	30	0.9	600	10 - 20	
150.0	-0/+1	171.5 ±2.0	10	30	0.9	700	10 - 20	

Tolerance on length: ±1% (ISO 1307 Standard).

* Stock item in Germany (Mettmann).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding



and embossed: TRELLEBORG - ALIKLER G2 - FDA - ND - WP 10bar - week/year - batch number - Made in France