

TRIX® SUPER

The high-grade water hose

TRIX® SUPER is the high-grade water hose for conveying water at high pressure. By easily handling working pressures up to 30 bar (435 psi), it is especially suitable for challenging applications like transporting pressure- and cooling water, but also for simple sprinkling, filling, discharging, rinsing and cleaning in industry, construction, municipal installations, farming, car pools, garages and workshops. The hose is very robust and has a low resistance to flow.

- Black, non-porous and smooth EPDM lining
- Reinforcements: synthetic fibres
- Black, smooth EPDM-cover, resistant to ozone, weather, UV and abrasion
- Working pressure up to 30 bar / 435 psi
- Temperature range from -40°C up to +120°C / -40°F up to +248°F
- Highly flexible, robust
- Release agent- and fat-free, free from any product harmful to lacquer
- Low resistance to flow
- Length independently electrically conductive, $R < 10^6 \Omega$



Technical Data

nominal width	Inner-Ø	wall thickness	length	working pressure		min. burst pressure		min. bending radius		weight
zoll / inch	mm	mm	m	bar	psi	bar	psi	aprx. mm		aprx. g/m
3/8	10	3,5	50	30	435	90	1305	35		225
1/2	13	4,0	50	30	435	90	1305	50		315
3/4	19	4,5	50	30	435	90	1305	65		480
1	25	5,0	50	30	435	90	1305	110		650

Pressure and vacuum based on room temperature / High pressure and/or temperature lead to reduced component durability