

## Medium Pressure Slimline Couplers

Slimline couplers are designed to be used **ONLY** for high pressure waterjetting applications, such as tube bundle cleaning.

Part Number	Description	Max Working Pressure
HCSL-MF4-LL	1/4" MP Female Slimline Coupler Left x Left* 0.374" OD	1,380 bar / 20,000 psi
HCSL-MF4-LR	1/4" MP Female Slimline Coupler Left x Right* 0.374" OD	1,380 bar / 20,000 psi
HCSL-MF4-RR	1/4" MP Female Slimline Coupler Right x Right* 0.374" OD	1,380 bar / 20,000 psi
HCSL-MF6-LL	3/8" MP Female Slimline Coupler Left x Left* 0.499" OD	1,380 bar / 20,000 psi
HCSL-MF6-LR	3/8" MP Female Slimline Coupler Left x Right* 0.499" OD	1,380 bar / 20,000 psi
HCSL-MF6-RR	3/8" MP Female Slimline Coupler Right x Right* 0.499" OD	1,380 bar / 20,000 psi
HCSL-MF9-LL	9/16" MP Female Slimline Coupler Left x Left* 0.687" OD	1,380 bar / 20,000 psi
HCSL-MF9-LR	9/16" MP Female Slimline Coupler Left x Right* 0.687" OD	1,380 bar / 20,000 psi
HCSL-MF9-RR	9/16" MP Female Slimline Coupler Right x Right* 0.687" OD	1,380 bar / 20,000 psi



\* Designates Left Hand Thread or Right Hand Thread