

Quick Disconnect Male Nipples with Check Valve

Part Number	Description	Max Working Pressure
SPC600-2-M9	Nipple with Check Valve x 9/16"-18 Type M	2,068 bar / 30,000 psi
SPC600-2-M12	Nipple with Check Valve x 3/4"-16 Type M	2,068 bar / 30,000 psi
SPC600-2-M16	Nipple with Check Valve x 1"-12 Type M	2,068 bar / 30,000 psi
SPC600-2-MJ4	Nipple with Check Valve x 1/4" JIC Male	690 bar / 10,000 psi
SPC600-2-MJ6	Nipple with Check Valve x 3/8" JIC Male	690 bar / 10,000 psi
SPC600-2-MJ8	Nipple with Check Valve x 1/2" JIC Male	690 bar / 10,000 psi
SPC600-2-NM4	Nipple with Check Valve x 1/4" NPT Male	1,035 bar / 15,000 psi
SPC600-2-NM6	Nipple with Check Valve x 3/8" NPT Male	1,035 bar / 15,000 psi
SPC600-2-NM8	Nipple with Check Valve x 1/2" NPT Male	1,035 bar / 15,000 psi
SPC600-2-NF4	Nipple with Check Valve x 1/4" NPT Female	1,035 bar / 15,000 psi
SPC600-2-NF6	Nipple with Check Valve x 3/8" NPT Female	1,035 bar / 15,000 psi
SPC600-2-NF8	Nipple with Check Valve x 1/2" NPT Female	1,035 bar / 15,000 psi
SPC600-2-MP4	Nipple with Check Valve x 1/4" MP Male	1,380 bar / 20,000 psi
SPC600-2-MP6	Nipple with Check Valve x 3/8" MP Male	1,380 bar / 20,000 psi
SPC600-2-MP9	Nipple with Check Valve x 9/16" MP Male	1,380 bar / 20,000 psi
SPC600-2-HP4	Nipple with Check Valve x 1/4" HP Male	2,068 bar / 30,000 psi
SPC600-2-HP6	Nipple with Check Valve x 3/8" HP Male	2,068 bar / 30,000 psi
SPC600-2-HP9	Nipple with Check Valve x 9/16" HP Male	2,068 bar / 30,000 psi
SPC600-2-X13	Nipple with Check Valve x Low Angle Male	2,068 bar / 30,000 psi

